

RTPL-4 Specification Table

Model	Center Frequency (MHz)	Bandwidth (MHz)	Output Level (dBm)	Dynamic Range (dB)	Input Power (dBm)
RTPL-4-1003	10	3	+10	80	-65 to +15
RTPL-4-3002	30	2	+10	80	-65 to +15
RTPL-4-3004	30	4	+10	80	-65 to +15
RTPL-4-3010	30	10	+10	80	-65 to +15
RTPL-4-4510	45	10	+10	80	-65 to +15
RTPL-4-6010	60	10	+10	80	-65 to +15
RTPL-4-6020	60	20	+10	80	-65 to +15
RTPL-4-7010	70	10	+10	80	-65 to +15
RTPL-4-7020	70	20	+10	80	-65 to +15
RTPL-4-12020	120	20	+10	70	-60 to +10
RTPL-4-12040	120	40	+10	70	-60 to +10
RTPL-4-16020	160	20	+10	70	-60 to +10
RTPL-4-16030	160	30	+10	70	-60 to +10
RTPL-8-16040	160	40	+10	70	-60 to +10

Additional Specifications	
Phase Shift	<+/-5°
Output Level	+10dBm +/- 1dB
Source Impedance	50 Ohms
Power Requirements	-15V DC
Connectors	SMA

Optional Specifications	
Hermetically Sealed Chassis	Change model # to RTPL-6 (requires RTL-6 chassis)
Power Supply	+/-12V DC (add suffix C)
Matched Set	2, 3 units/set (add suffix M)