

RTPL-8 Specification Table

Model	Center Frequency (MHz)	Bandwidth (MHz)	Output Level (dBm)	Dynamic Range (dB)	Input Power (dBm)
RTPL-8-1003	10	3	0	70	-60 to +10
RTPL-8-3002	30	2	0	70	-60 to +10
RTPL-8-3004	30	4	0	70	-60 to +10
RTPL-8-3010	30	10	0	70	-60 to +10
RTPL-8-4510	45	10	0	70	-60 to +10
RTPL-8-6010	60	10	0	70	-60 to +10
RTPL-8-6020	60	20	0	70	-60 to +10
RTPL-8-7010	70	10	0	70	-60 to +10
RTPL-8-7020	70	20	0	70	-60 to +10
RTPL-8-12020	120	20	0	60	-50 to +10
RTPL-8-12040	120	40	0	60	-50 to +10
RTPL-8-16020	160	20	0	60	-50 to +10
RTPL-8-16030	160	30	0	60	-50 to +10
RTPL-8-16040	160	40	0	60	-50 to +10

Additional Specifications	
Phase Shift	<+/-5°
Output Level	0dBm +/-1dB
Source Impedance	50 Ohms
Power Requirements	-15V DC
Connectors	SMA

Optional Specifications	
Power Supply	-12V DC (add suffix C)
Matched Set	2, 3 units/set (add suffix M) <5° tracking